GC1710 TLB GARDEN COMPACT

MASSEY FERGUSON®

(F.O.B. Port of Entry)

TRACTOR FEATURES

POWER TRAIN

- Engine:
  22.5 Gross HP 3 Cyl Diesel 68.5 CID (1.1 L)
  22.0 Net HP @ 2600 RPM
  18.7 PTO HP @ 2600 RPM
- Dry Type Single Air Cleaner
- Transmission: 2 Range Hydrostatic with Cruise Control
- Wet Disk Brakes
- Parking Brake
- Differential Lock
- PTO: 540 RPM Independent PTO
  2000 RPM Mid Independent PTO

HYDRAULIC SYSTEM

- 3-Point Hitch, Cat I With Directional Control, Auto Return Lever System
- Engine Driven Gear Pump
- 3-Point Hitch 4.3 GPM (16.5 LPM)
- Power Steering 2.0 GPM (7.5 LPM)
- Total Combined Flow 6.3 GPM (24 LPM)

INSTRUMENTS

- Tachometer / Hourmeter
- Engine Coolant Gauge Fuel Gauge
- Warning Lights: Electrical Charging, Oil Pressure and Water Temperature

OTHER STANDARD FEATURES

- Hydrostatic Power Steering
- Hand Accelerator
- Forward And Reverse Foot Pedal
- Electric Fuel Shut-Off
- 12 Volt Electrical System
- Battery: 390 Cold Cranking Amps
- Full Adjustable Seat With Retractable Seat Belt
- 2 Post Folding Rops
- Tilt-Up Hood
- Turn Signals, Flashers, Tail Lights
- Factory Joystick
- Hydraulic Manifold with Pressure and Return Lines on Model with Factory Joystick

- ***Note: 3-Point Mounted Backhoe Installation Voids Warranty. Use the Required Subframe Mounting Kit.***

IMPLEMENT FEATURES

MF DL95 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 1.6 inch Double Acting Lift Cylinders
- (2) 1.75 inch Double Acting Bucket Cylinders
- Regenerative Hydraulics for Simultaneous Operation of Lift/Lower and Curl/Dump Functions
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- 48-inch Standard Duty Pin-Type Bucket
- Grille Guard Standard
- Maximum Lift Height: 72.8 Inches
- Lift Capacity to Full Height @ 19.6 inches Forward of Pivot Pin: 580 lbs
- Breakout Force: 920 lbs
- Rated Hydraulic Pressure: 1914 PSI
- Fits all GC1700 Series Tractors

MF CB65 BACKHOE

- Digging Depth: 78 inch (2.0 m)
- Max Reach: 107 inch (2.7 m)
- Transport Height: 71 inches (1.8 m)
- Stabilizer Spread - Transport: 47 inch (1.2 m)
- Stabilizer Spread - Operating: 80 inch (2.0 m)
- Loading Height: 66 inch (1.7 m)
- Angle of Departure: 20 Degrees
- Swing Arc: 150 Degrees
- Bucket Rotation: 177 Degrees
- Shipping Weight: 635 lbs (288 kg)
- Digging Force Using Bucket Cylinder: 2476 lb (1123 kg)
- Digging Force Using Dipper Cylinder: 1748 lb (793 kg)
- Single Cylinder Boom Swing

NOTE: Dimensions may change due to tire size

AVAILABLE ATTACHMENTS (REFER TO IMPLEMENT SECTIONS)

- MF 2315, 2320, 2326 Mid Mounted Mowers
- MF 2360 Front Mounted Snow Blower
- MF 2330 Front Mounted Rotary Broom
- MF 2335 Front Mounted Blade
- MF 2340 Front Mounted Heavy Duty Blade