



GC1723E TLB GARDEN COMPACT

TRACTOR LOADER BACKHOE

(F.O.B. Port of Entry)

TRACTOR FEATURES

POWER TRAIN

- Engine:
 - 22.5 Gross HP 3 Cyl Diesel
 - 1.12 L Displacement
 - 21.6 Net HP @ 2600 RPM
 - 18.3 PTO HP @ 2600 RPM
- Dry Type Single Air Cleaner
- Transmission: 2 Range Hydrostatic with Cruise Control
- Wet Disk Brakes
- Parking Brake
- Differential Lock
- PTO: 540 RPM Independent PTO
2000 RPM Mid Independent PTO

HYDRAULIC SYSTEM

- 3-Point Hitch, Cat I With Directional Control, Auto Return Lever System
- Engine Driven Gear Pump
- 3-Point Hitch 4.3 GPM (16.5 LPM)
- Power Steering 2.0 GPM (7.5 LPM)
- Total Combined Flow 6.3 GPM (24 LPM)

INSTRUMENTS

- Tachometer / Hourmeter
- Engine Coolant Gauge Fuel Gauge
- Warning Lights: Electrical Charging, Oil Pressure and Water Temperature

OTHER STANDARD FEATURES

- Hydrostatic Power Steering
- Tilt Steering Column
- Hand Accelerator
- Forward and Reverse Foot Pedal
- Rubber Floor Mat
- Covered Storage Compartment
- Electric Fuel Shut-Off
- 12 Volt Electrical System
- Battery: 390 Cold Cranking Amps
- Fully Adjustable Seat With Retractable Seatbelt
- 2 Post Folding Rops
- Tilt-Up Hood
- Turn Signals, Flashers, Tail Lights
- Factory Joystick
- Hydraulic Manifold with Pressure and Return Lines on Model with Factory Joystick

- **Note: 3-Point Mounted Backhoe Installation Voids Warranty. Use the Required Subframe Mounting Kit.**

IMPLEMENT FEATURES

MF FL1805 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 1.57 inch Double Acting Lift Cylinders
- (2) 1.57 inch Double Acting Bucket Cylinders
- Simultaneous Operation of Lift/Lower and Curl/Dump Functions
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Pins with Recessed Grease Points
- 48-inch Standard Duty Skid Steer Bucket
- Grille Guard Standard
- Maximum Lift Height at Pivot Pins: 74 Inches
- Lift Capacity to Full Height at Pivot Pins: 922 lbs
- **Lift Capacity 19.5" Forward of Pins: 622 lbs**
- Breakout Force at Pivot Pins: 1,392 lbs
- Rated Hydraulic Pressure: 1,920 PSI
- Fits all GC1700 Series Tractors

MF BH2720 BACKHOE

- Digging Depth: 76 inches (1.9 m)
- Max Reach: 107 inches (2.7 m)
- Transport Height: 71 inches (1.8 m)
- Stabilizer Spread - Transport: 51 inches (1.3 m)
- Stabilizer Spread - Operating: 81 inches (2.1 m)
- Loading Height: 66 inches (1.7 m)
- Angle of Departure: 22 Degrees
- Swing Arc: 150 Degrees
- Bucket Rotation: 177 Degrees
- Shipping Weight: 573 lbs (260 kg)
- Digging Force Using Bucket Cylinder: 2184 lbs (911 kg)
- Digging Force Using Dipper Cylinder: 1541 lbs (699 kg)
- Single Boom Swing Cylinder

NOTES: *Dimensions may change due to tire size. Backhoe must be detached before installing the mid mount mower.*

AVAILABLE ATTACHMENTS (REFER TO IMPLEMENT SECTIONS)

- MF 2315, 2320, 2326 Mid Mounted Mowers (*Backhoe must be removed to operate mid mount mower.*)
- MF 2360 Front Mounted Snow Blower
- MF 2330 Front Mounted Rotary Broom
- MF 2335 Front Mounted Blade
- MF 2340 Front Mounted Heavy Duty Blade

April 2024