

# GC1725M GARDEN COMPACT

(F.O.B. Port of Entry)

## TRACTOR FEATURES

### POWER TRAIN

- Engine:
  - 24.5 Gross HP 3 Cyl Diesel
  - 1.12 L Displacement
  - 23.6 Net HP @ 3000 RPM
  - 18.5 PTO HP @ 3000 RPM
- Dry Type Single Air Cleaner
- Transmission: 2 Range Hydrostatic with Cruise Control
- Wet Disk Brakes
- Parking Brake
- Differential Lock
- PTO: 540 RPM Independent PTO  
2000 RPM Mid Independent PTO

### HYDRAULIC SYSTEM

- 3-Point Hitch, Cat I With Directional Control, Auto Return Lever System
- Engine Driven Gear Pump
- 3-Point Hitch 4.9 GPM (18.8 LPM)
- Power Steering 2.0 GPM (7.5 LPM)
- Total Combined Flow 6.9 GPM (26.3 LPM)

### INSTRUMENTS

- Tachometer / Hourmeter
- Engine Coolant Gauge Fuel Gauge
- Warning Lights: Electrical Charging and Oil Pressure and Water Temperature

### OTHER STANDARD FEATURES

- Hydrostatic Power Steering
- Tilt Steering Column
- Hand Accelerator
- Forward And Reverse Foot Pedal
- Rubber Floor Mat
- Covered Storage Compartment with 12V Socket
- Electric Fuel Shut-Off
- 12 Volt Electrical System
- Battery: 390 Cold Cranking Amps
- Fully Adjustable Swivel Seat with Armrests and Retractable Seatbelt
- 2 Post Fixed ROPS
- Tilt-Up Hood
- Turn Signals, Flashers, Tail Lights
- Factory Joystick
- Hydraulic Manifold with Pressure and Return Lines on Model with Factory Joystick

- **Note: 3-Point Mounted Backhoe Installation Voids Warranty. Use the Required Subframe Mounting Kit.**

## IMPLEMENT FEATURES

### MF FL1805 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 1.57 inch Double Acting Lift Cylinders
- (2) 1.57 inch Double Acting Bucket Cylinders
- Simultaneous Operation of Lift/Lower and Curl/Dump Functions
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Pins with Recessed Grease Points
- 48-inch Standard Duty Skid Steer Bucket
- Grille Guard Standard
- Maximum Lift Height at Pivot Pins: 74 Inches
- Lift Capacity to Full Height at Pivot Pins: 922 lbs
- [Lift Capacity 19.5" Forward of Pins: 622 lbs](#)
- Breakout Force at Pivot Pins: 1,392 lbs
- Rated Hydraulic Pressure: 1,920 PSI
- Fits all GC1700 Series Tractors

### AVAILABLE ATTACHMENTS (REFER TO IMPLEMENT SECTIONS)

- MF 2315, 2320 and 2326 Mid Mounted Mowers
- MF 2360 Front Mounted Snow Blower
- MF 2330 Front Mounted Rotary Broom
- MF 2335 Front Mounted Blade
- MF 2340 Front Mounted Heavy Duty Blade

**April 2024**