



HESSTON

1393 CENTER PIVOT DISC MOWER CONDITIONER

FOB Hesston, KS

STANDARD EQUIPMENT

RazorEdge™ Welded One-piece Cutterbed
Working Width 13' (3.9m)
8 Discs (2450 RPM)
Disc diameter 24.5"
Spur Gear Cutterbed Design Utilizing in House
Forged Gears from the AGCO Power Foundry
Swath Width 40" to 96" (1m to 2.4m)
Transport Width 159" (4.0m)
12.5L x 15 Tires
16 Knives - Swing-away, Reversible
1000 PTO - Gearbox Swivel Hitch w/ Slip
Overrunning Clutch
Cutting Height 3/4" to 3" (19mm- 76mm)
Smooth Rock Guards
Top Shield Protector
1-3/8" 21 Spline PTO Shaft

Conditioner Drive - Enclosed Spur Gear with U-Joint Drive Shafts
110" (2.8m) Roller Conditioner Herringbone Steel on Steel Rolls
110" (2.8m) Rubber on Steel Herringbone Rolls - Optional
110" (2.8m) Turbulence Reduction Roll
Hydraulic Conditioner Roll Tension
Auto Header Tilt with Lower Feature- Hydraulic Adjust
Rooding Lock
Hitch Jack
Hydraulic Tongue Control

Tractor Requirements

100 PTO HP minimum with Fully Enclosed ROPS Cab
Two Double Acting Remote Valves

MAY 2024