



1395 CENTER PIVOT DISC MOWER CONDITIONER

FOB Hesston, KS

STANDARD EQUIPMENT

RazorEdge™ Spur Gear Cutterbed

Working Width 16' (4.9m)

10 Discs (2450 RPM)

Disc diameter 24.5"

Modular Spur Gear Cutterbed Design

Swath Width 40" to 96" (1m to 2.4m)

Transport Width 16.25 ft (5m)

31 x 13.5 x 15 Tires

Disc Drive - 4HA Banded Belt to End of Cutterbed

20 Knives - Swing-away, Reversible

1000 PTO - Gearbox Swivel Hitch w/ Slip

Overrunning Clutch

Cutting Height 3/4" to 3" (19mm- 76mm)

Smooth Rock Guards

Top Shield Protector

1-3/8" 21 Spline PTO Shaft

Conditioner Drive -Enclosed Spur Gear with U-Joint Drive Shafts

110" (2.8m) Roller Conditioner Herringbone Steel on Steel Rolls

110" (2.8m) Rubber on Steel Herringbone Rolls Optional

110" (2.8m) Turbulence Reduction Roll

Hydraulic Conditioner Roll Tension

Auto Header Tilt with Lower Feature- Hydraulic Adjust

Roading Lock

Hitch Jack

Hydraulic Tongue Control

Two Adjustable Skid Shoes

Tractor Requirements

120 PTO HP minimum with Fully Enclosed ROPS Cab

Two Double Acting Remote Valves