

MF 1526H



(F.O.B. Port of Entry)

FEATURES

POWER TRAIN

- Engine:
 - 24.8 Gross HP Iseki 3-Cylinder Diesel
 - 1.49 L Displacement
 - 20.1 PTO HP @ 2600 RPM
 - Dry Single Element Air Cleaner
 - EPA and CARB Certified
 - Emission Standard Category: Tier 4 Final
- Transmission:
 - Hydrostatic: with 3 Non-Synchronized Ranges and Cruise Control with Auto-Throttle Control
- Wet Disc Brakes, Parking Brake
- Differential Lock: Foot Pedal Operated
- PTO:
 - Rear - 540 RPM Independent Electro Hydraulic
 - Mid - Optional 2000 RPM Independent through Parts

HYDRAULIC SYSTEM:

- 3-Point Hitch Cat I with Position and Response Control
- Lift Capacity @ 24 inches: 992 lbs
- Dual Engine Driven Gear Pumps
- Flow @ Remotes 5.5 GPM (20.8 LPM)
- Power Steering Pump 3.2 GPM (12.1 LPM)
- Total Combined 8.7 GPM (32.9 LPM)
- Can Support Single Rear Remote Valve (Optional, Field Installed)

INSTRUMENTS:

- Tachometer and Hour Meter
- Temperature and Fuel Gauges
- Warning Lights: High Beam indicator, Battery Charge (alt) Indicator and Flasher Indicators
- Key Operated Electronic Fuel Shutoff and Glow Plug Control

OTHER STANDARD FEATURES:

- Turn Signals, Flashers, Tail Lights, SMV Emblem
- Turn Buckle Stabilizers
- Hydrostatic Power Steering
- Foot Accelerator
- Hand Accelerator
- 2 Post Folding Rops and Retractable Seat Belt
- Removable Side Panels
- Side Shift Control Levers
- Adjustable Suspension Seat
- Tilt Hood

- **Note: 3-Point Mounted Backhoe Installation Voids Warranty.**

IMPLEMENT FEATURES

MF FLX2106 LOADER

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 1.77 inch Double Acting Lift Cylinders
- (2) 1.77 inch Double Acting Bucket Cylinders
- Simultaneous Operation of Lift/Lower and Curl/Dump Functions
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Pins
- Recessed Grease Zerk Points
- 54-inch Standard Duty Pin-Type Bucket
- Grille Guard Standard
- Fits MF1526 with Turf or R4 Tires
- Maximum Lift Height at Pivot Pins: 83 Inches
- Lift Capacity to Full Height at Pivot Pins: 1,222 lbs
- Lift Capacity 19.5" Forward of Pins: 852 lbs
- Breakout Force at Pivot Pins: 1,870 lbs
- Rated Hydraulic Pressure: 2,132 PSI
- Maximum Roll Back Angle: 31 Degrees
- Dump Angle: 42 Degrees

April 2024