



HESSTON

2956A ROUND BALER

FOB Hesston, KS

STANDARD EQUIPMENT

On-Board Hydraulic System
61.5" (1.6m) Wide x 72" (1.8m) Diameter Bale
80.6" (2m) Wide Pickup Assembly - Dual CamTrack Tine Control
Pickup Wind Guard
Slip Clutch with Hydraulic Declutcher
Bale Counter
Bale Size Indicator
"Bale Full" Audio and Visual Alert
3 Bar Color Coded Bale Shape Indicator
Direct Feed, Rotor, Open Throat Chamber
540/1000 RPM PTO Drive
Hydraulic Pickup Lift
Extra Mesh Roll Storage
Over the Edge Mesh Wrap Capabilities
Twine Tie and Mesh Wrap
QCS - Quad Cylinder Bale Density System
21.5L-16.1 Tires with Suspension Axle

Automatic Tying when Preset Bale Size is reached
with Manual Override
Dual Tube Twine Arm
Staggered Belt Clean Out
Wedge Grip Belts with Alligator Lacings
Electrically Activated Twine and Mesh Wrap Systems
Safety Chain
Warning Light (Flashing)

Tractor Requirements

70 PTO HP (minimum)
One Double Acting Remote Valve
Bale Control Monitor required to Operate Baler
See Group 98

JANUARY 2023