MFFL.3522 / MFFL.3615 LOADERS

NON SELF-LEVELING / MECHANICAL SELF-LEVELING



(F.O.B. Simpsonville, SC with Distribution Center in Alliston, Ontario)

FEATURES

· Compatible with MF 4700 Global Series Tractors

FL.3522 Non-Self Leveling

- 139.8 in. (3550mm) Max Lift Height at Pivot Pins
- 4,410 lb. (2000kg) Lift Capacity to Max Lift Height at Pivot Pins
- **2,760 lb. (1250kg)** Lift Capacity to Max Lift Height, 31.5 in. (800mm) Forward of Pivot Pins
- 4,890 lb. (2220kg) Lift Capacity to 59 in. (150mm) Lift Height at Pivot Pins
- 3,640 lb. (1650kg) Lift Capacity to 59 in. (150mm) Lift Height, 31.5 in. (800mm) Forward of Pivot Pins

- FL.3615 Mechanical Self Leveling
 139.8 in. (3550mm) Max Lift Height at Pivot Pins
- 3,020 lb. (1370kg) Lift Capacity to Max Lift Height at Pivot Pins
- **3,420 lb. (1550kg)** Lift Capacity to Max Lift Height, 31.5 in. (800mm) Forward of Pivot Pins
- 3,400 lb. (1540kg) Lift Capacity to 59 in. (150mm) Lift Height at Pivot Pins
- 3,460 lb. (1570kg) Lift Capacity to 59 in. (150mm) Lift Height, 31.5 in. (800mm) Forward of Pivot Pins

- · Construction
 - ▶Welded C Section Loader Beams with Internally Routed Hydraulic Hoses for Neat Concealment and Protection
 - ▶Tough and Durable Powder Coat Finish Ensuring Long Life
- Requiring No Tools and Rigid Support Legs
- Easy and Fast Hydraulic Connection
 Connection of the Tractor and Loader is Made Easy by Compact Design of Flat Face Couplings
 - ▶For Faster Hydraulic Connection, Simple Action Multicouplers are Available
- SoftDrive
 - ► Shock Absorption System that Reduces Stresses on the Loader, Tractor, as Well as the Operator ► Hidden and Protected inside the Cross Tube,
 - SoftDrive can be Electronically Activated When you Need It

NOTE: TRACTORS MUST BE PROPERLY BALLASTED FOR LOADER OPERATION. SEE OPERATOR'S MANUAL

NOTE: SPECIFICATIONS MAY VARY BETWEEN MODELS, TIRE EQUIPMENT AND HYDRAULIC OPTIONS

FOR MORE INFORMATION ON DEALER INSTALLED LOADER OPTIONS SEE PAGE 70