



MF4608

MASSEY FERGUSON®

(F.O.B. PORT OF ENTRY)

TRACTOR FEATURES

ENGINE SYSTEM

- Engine: AGCO Power 33AWIC 3 Cylinder (Turbocharged)
80 Engine HP (60 kW) @ 2200 RPM
63.5 PTO HP (47.4 kW) @ 2000 RPM
- EPA Tier 4i Compliant
- Air Cleaner: Dual Element Dry Type
- Air Cleaner Intake, Under Hood
- Vertical Exhaust, Side of Hood
- Cooling System: Antifreeze 50/50 Mix

FRONT AXLE

- 2wd: Adjustable
- 4wd: Center Driveline, Open Differential, Mechanical Engagement

POWER TRAIN

- Transmission:
12 X 12 Power Shuttle with Left Hand Shuttle Lever
6 Synchronized Gears, 2 Ranges
Wet Multi-disc Clutch with Left Side Clutch Pedal
- Rear Axle: Inboard Planetary Final Drives, with Foot Operated Mechanical Differential Lock
- Brakes: Independent Oil Immersed Wet Disc Brakes with Independent Foot Pedal Operation
- Hook and Lever Parking Brake
- PTO: Independent 540 and 1000 RPM Speeds, 6 Spline Shaft and 21 Spline (1.375 In. Diameter), Independent Wet Disc Clutch, Electro-hydraulic Engagement

HYDRAULIC SYSTEM

- Steering: Hydrostatic, Adjustable Tilt Steering Column
- Implement System:
Open Center System, Engine Driven Gear Pump
17.1 GPM (65 LPM) flow to Remotes
Optional Integrated Cable-controlled Loader Joystick with Mid Valves
- Rear Linkage:
ASAE Category II with Telescopic Ball Ends
Shared Pump with Implements
Lift Capacity at 24": 3417 LBS (1550 KG)
Adjustable Lift Rod, Turn Buckle Top Link
Telescopic Stabilizers
- Swinging Drawbar

ELECTRICAL

- 12 Volt DC, Negative Ground
- Intake Air Pre Heater
- Wet, Maintenance Free 799 CCA Battery
95 AMP Alternator
- Ignition: Key with Safety Start
- Keyed Engine Shutoff
- Lighting: 4 Headlights, 2 Rear Marker Light Assemblies
- 7 Pin ASAE Outlet Socket

INSTRUMENTS

- Digital and Analog Dash Display
- Analog Engine Tachometer
- Digital Fuel Gauge
- Digital Engine Temperature
- Digital Transmission Display
- Digital Hour Meter
- Operation and Service Lights

OPERATORS ENVIRONMENT (Platform Models)

- Flat Floor Platform
- Folding ROPS
- Seat: Adjustable Spring Cushion Vinyl with Armrests
- Retractable Seat Belt
- Pendant Style (Suspended) Foot Pedals
- Hand and Foot Throttle
- Left Side Foot Step

OPERATORS ENVIRONMENT (Cab Models)

- 6-post Cab With HVAC, Tinted Safety Glass, Front Windshield Wiper/Washer, Front and Rear Roof-mounted Working Lights, 2 Doors, Pre-wired for Audio System
- Right and Left Side View Mirrors
- Seat: Adjustable Spring Cushion with Armrests
- Retractable Seat Belt
- Pendant Style (Suspended) Foot Pedals
- Hand and Foot Throttle
- Left and Right Side Foot Step

OTHER STANDARD FEATURES

- Fuel Tank Under Platform, Ground Fill
Fuel Capacity: 27.7 gallons (105 Liters)
- One-Piece Tilting Hood
- Tool Box
- SMV Emblem

LOADER FEATURES

MF921X Loader

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.6 inch Double Acting Lift Cylinders
- (2) 2.6 inch Double Acting Bucket Cylinders
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- Universal Skid Steer or Euro Hook Type Implement Attachments
- Grille Guard Standard
- Fits MF4608 4wd Tractor Models
- Rated on MF4608 Tractor with 9.5-24 Front Tires and 16.9-30 Rear Tires
- Lift Capacity to Full Height @ 31.5 inches Forward of Pivot Pin: 1920 lbs
- Maximum Lift Height: 124 inches at Pivot
- Breakout Force: 3200 lbs
- Rated Hydraulic Pressure: 2828 PSI