

# **400D CLASSIC EDITION**

(F.O.B. PORT OF ENTRY)

### **CLASSIC EDITION FEATURES**

### **ENGINE**

# MT455D/MT465D/MT485D/MT495D

AGCO POWER™ 4.9L (299 cu in.) 4 Cylinder, Tier 4i Compliant

- SCR Technology
- Air-to-Air Aftercooled, Common Rail Injection, Turbocharged

Electronic Engine Management (EEM) with Dual ERPM Settings

Electronic Controlled Viscous Fan Drive Dual Element Dry Type Air Cleaner Vertical Exhaust at Right Front Cab Post Cooling System: Antifreeze to Minus 30F (-34C)

Fuel Tank Capacity: 64 Gal (242L) DEF Tank Capacity: 9.2 Gal (35L)

#### **POWERTRAIN**

### MT455D/MT465D/MT485D: AutoPower IV Transmission

 16F/16R Semi-Powershift, 4 Ranges with 4 Powershifts Per Range

### MT495D: AutoPower VI Transmission

 24F/24R Semi-Powershift, 4 Ranges with 6 Powershifts per Range

Multi-Disc Wet Brakes

Power Differential Lock

Independent PTO: 540/1000 RPM, 540 with 6 Spline Shaft, 1000 RPM with 21 Spline Shaft, Exchangeable Shafts

Rear Fender Mounted PTO Shut-Off

Flange Axles

### FRONT WHEEL ASSIST AXLE

Power Front Axle (PFA)

- 8 Bolt Pattern: MT455D/MT465D/MT485D: AutoPower IV/AutoPower VI
- 10 Bolt Pattern: MT495D AutoPower VI

Shielded Center Drive Line with Electro-Hydraulic Control and Front Wheel Drive Differential Lock

55 Degree Steering Angle

# **HYDRAULICS**

Closed Center Load Sensing 29 GPM (110 L/Min) Pump 2900 PSI (200 Bar) Maximum Pressure 3 Mechanical Valves – Lever Controlled on Right Hand Console Hydrostatic Power Steering

### **HITCH**

3-Point Hitch: Category 2/3 Linkage Ball Ends

- 11,400 lbs lift capacity @ 24"
- · Active Transport Control
- · Lower Link Sensing
- Electronic Draft Control, Electronic Height Control, and Rate of Drop
- · Variable Float Telescopic Stabilizers
- · Left and Right Side External 3 Point Control

Drawbar: Category 2, Clevis and Drop Pin

#### **ELECTRICAL SYSTEM**

175 Amp Alternator
2 – 12V Batteries, 600 CCA Each (SAE)
7 Pin ASAE Rear Trailer Electrical Outlet
Electrical Isolator Switch and Jumpstart Point
110V Engine Block Heater
Ignition with Neutral Start and Key Shutoff

#### LIGHTING

8 Front Hood Mounted Lights
Four Front Single Bulb Worklights
Two Rear Double Bulb Worklights
Tail Lights, Flashing Warning Lights and Turn Signals

### **INSTRUMENTS**

Tachometer: Digital and Analog PTO Speed: Digital Ground Speed Display: Digital

Fuel Level, DEF Level, and Coolant Temp Gauges

Warning/Information Lights

## **OPERATOR AREA**

6 Post Cab

Transmission Control T-Handle on Right Hand Console Adjustable Steering Column

Front Sun Visor

Air Conditioning and Heater

Air Suspended Seat - Manual Adjustment Front and Rear Windshield Wiper/Washer

Dual Large Telescoping Outside Rear View Mirrors

Single Inside Rear View Mirror 2 Audio Speakers and Antenna 3 Pin 12V Power Outlets

12V Cigarette Lighter Style Power Outlet

# WHEELS AND TIRES

Rear 460/85R38 R1W Single Wheels Front 380/85R28 R1W Single Waffle Wheels

### **OTHER STANDARD FEATURES**

AGCOMMAND™ Ready with Antenna, Bracket, and Harness (No Module or Subscription)
(To Complete, See Technology Section)

Lockable Tool Box

SMV Sign

Molded Rear Fenders English Literature

MT400D models with AutoPower VI Transmission can not be sold in Nebraska