



STANDARD EQUIPMENT F.O.B. JACKSON, MN

MT700E

MODELS

- **MT755E:** 355 Rated Engine HP
- **MT765E:** 380 Rated Engine HP
- **MT775E:** 405 Rated Engine HP

POWER TRAIN

- AP98-4: AGCO POWER 9.8L Tier 4F, 7 Cylinder Diesel Engine
- Water Separator and Fuel Filter
- Suction Type Viscous Fan
- Side Mounted Muffler with Integrated SCR Catalyst (Mounted on Right Hand Corner of Cab)
- Automatic Starting Aid, Intake Grid Heater
- Venturi-Type Engine Air Pre-Cleaner
- Two-Stage Cassette-Type Engine Air Filter
- Two Plane Stacked Cooling Package
- Powershift Transmission, 16 Forward / 4 Reverse with Electronic Controls
- Power Management Modes:
Max Output and Constant Ground Speed
- Shuttle Shift Capabilities
- Inching Control Pedal

UNDER CARRIAGE

- Standard Gauge, 72" to 88" (1524 mm - 2235 mm)
- Narrow Width Rubber Front Idlers
- Medium Width Rubber Rear Driver Wheels
- Medium Width Poly Midwheels
- 18" Chevron General Ag Tracks
- Mounting Points for Accessory Tanks

HYDRAULICS

- Four Electro-Hydraulic Implement Valves with Fingertip Controls and One 3-Point Hitch Valve Includes: Raise, Lower and Float Detents
- Automatic Kickout from Raise and Lower Activation
- Closed Center Load Sensing Pressure Compensation
- 58 GPM Pump with 2900 PSI Main Relief System
- SOS Sampling Port: Hydraulic & Transmission Oil
- Power Beyond with 3/4" Couplers & Load Sense Line

ELECTRICAL

- Full ISO 11783 Compatible Wiring and Electronics with 9-Pin ISO connector
- Two 12V, 150 amp Alternators
- Six Outlet Power Strip (30 Amp, 12 Volt) & Three Single Pole Power Outlets (10 Amp, 12 Volt) in cab
- One 12 Volt Single Pole Outlet on rear of tractor
- Two 12 Volt, 1000 CCA, Maintenance Free Batteries
- Halogen Lamps:
HOOD - Two Low Beam, Two High Beam, Two Side Floods
TRACKLINE - Two Floods
CAB ROOF - Eight Floods, Rear Facing
REAR FENDERS - Reverse Lights, Tail and Brake Lights
- Battery Disconnect Switch
- Radar with Slip Control and Performance Monitor Activation
- 2 Strobing Beacons with Roof Mounting Brackets

OPERATOR ENVIRONMENT

- Four Post Pinnacle View Cab with ROPS and Sound Suppression
- Air Conditioner
- Heater and Defroster
- 2 Beverage Holders, Storage Box, Floor Mat, Coat Hook, Storage for Literature
- Horn
- Cigar Lighter
- 2 USB Smart Charge Ports
- 1 Aux Input
- Interior Courtesy Lights
- Accessory Mounting Bar
- Single Spoke Tilt and Telescoping Steering Wheel
- Rear View Mirror
- Tinted Glass
- Parallel Sweeping Front Wiper with Intermittent setting
- Tractor Management Center (TMC) Located on Right Side of Operator Seat, Adjusts Fore / Aft Relative to Seat, Includes Arm Pad with Storage and TMC Display. Contains Fingertip Controls for: PTO, 3-Point Hitch, Electro-Hydraulic Implement Controls, One Touch System, Transmission, Throttle, Rooding Lockout
- Fully Adjustable Seat: Air Suspension with Vertical Height and Backrest Angle Adjustment, Fore & Aft / Side to Side Isolators, Lumbar Support, Seat Belt, and Adjustable Left Armrest
- Instructional Seat: Cushioned with Desk Surface, Beverage Holder, and Seat Belt
- Gauges: Engine Coolant Temperature, Engine Oil Pressure, Hydraulic Oil Temperature, Tachometer, Fuel, DEF
- Dash Indicators: High Beam and Tractor Lights
- AM/FM Weatherband Radio with Bluetooth / USB
- Integrated Bluetooth microphone

OTHER STANDARD EQUIPMENT

- Auto-Guide™ 3000 Ready
- AGCOMMAND™ Telemetry System with 1 Year Subscription (Must be activated within 12 months of warranty registration)
- Slow Moving Vehicle Emblem
- Fenders with External 3-Point Hitch Control
- Pivoting Front Step to Cab
- 179 Gallon (677 liter) Fuel Tank
- 23 Gallon (87 liter) Diesel Exhaust Fluid (DEF) Tank
- PTO: 1000 RPM, 1.75" (44 mm) 20 Spline Shaft
- Narrow Swinging Category IV Drawbar with Clevis and Category III Pin Adapter
- 3-Point Hitch with Category III/IVN Quick Hitch
- 16,000 Lbs Lift Capacity with Transport Dampening System
- Integrated Toolbox in Entry Platform
- Hydraulic Tensioning Hose for MTS
- Hood Service Support Bar